

KTXV Void Security Tape



KTXV Security tape is a low cost alternative to the TydenBrooks KTL range of packaging/parcel tape. It carries a standard VOID/OPENED security message and a plain, unbranded, surface. Attempts to remove or lift the tape will result in the VOID/OPENED message being clearly displayed. Ideal for "pallet wrap" sealing.

APPLICATIONS

- Fibre cartons
- Cardboard
- Wooden Boxes/creates
- Waxed Cartons
- Boxes Pallets
- Shrink/pallet Wrap

FEATURES

- Suitable for a wide range of applications
- Self wound BLUE voiding packing tape
- Available in from stock 50mm x 50m plain
- Standard VOID OPENED void message
- Can be personalised to instruction on larger quantities
- TSA approved for CCSP (USA)
- Can be used with a standard 50mm/2" tape dispenser

MATERIAL SPECIFICATION

- Material Spec available on Page 2

PRINT/SIZE OPTIONS

- Available as stock tape 50mm x 50m Blue
- Can be personalised to instruction with customers logo/name, m.o.q 400 rolls

PACKING DETAILS

Supplied in rolls of 50mm x 50m (2" x 164"); 50 rolls per carton
 Carton L580mm x W240mm x H310mm; Weight 10.5 Kgs



ASIS14 accolades Winner PEOPLE'S CHOICE AWARD FOR MOST INNOVATIVE PRODUCT

Seals shown not actual size.



KTXT Void Security Tape



Product Code	DTXT
Product	Total Transfer Security Tape for Carton
Size	50mm x 50m roll
Liner	Glassine paper 80g/m ²
Carrier	PET film, thickness of 0.025mm/25micron
Product Description	Acrylic resin, pressure sensitive
Description	Heavy adhesion, high holding power, hidden message will show once tear off the tape. Trace Performance: over 96%
Range of Application	Used to seal any kind of normal cartons or boxes. * (Non-resealable label)
Color	Standard color: blue and red. It is also available for customized a special requirement from customers.
Application Temperature	10°C ~ 60°C

Characteristics	
Total Thickness	25u
Adhesive Thickness	50u
Initial Tack	<11 cm
Holding Power	>24hrs (0.5kg/2.5cm*2.5cm)
Remarks	(1) Testing conditions ± lab temperature 25± 5° and lab humidity 55%. (2) Preserve a constant temperature 15°C ~30° C store in shady place and avoid exposing to high temperature or sunshine condition. (3) Under normal condition, it could be preserved for eight months. (4) Also available for customized, special requirement from customers.