



# DUAL FLEX SEAL

The Dual Flex Cable Seal is a double locking seal that offers an increased level of tamper protection. It is High Security rated per the ISO 17712:2013 testing standard and is C-TPAT compliant. It is suitable for many applications and is popular for sealing bulk railcars and intermodal containers and trailers. The non-preform cable frays wildly when cut and is galvanized for corrosion protection.

## APPLICATIONS

- Cross Border Shipments
- Container Door Latches
- High Value Shipments
- Rail Cars
- Trailer Door Latches

## FEATURES

- Dual locking helps prevent ratcheting and shimming
- Tamper-evident non-preformed steel cable unravels when cut and is galvanized for corrosion protection
- Customized laser printing name/logo/consecutive numbers and bar code

## MATERIAL

- Main body: Aluminum alloy
- Internal Locking Components: Zinc and Steel
- Cable: 4.0 mm galvanized non-preformed cable

## STRENGTH CHARACTERISTICS

- Average pull apart strength: 3,000 lbs (13.3 kN)

## DIMENSIONS

- Body: 1.69" x 1.38" x .39" (43mm x 35mm x 10mm)
- Cable Diameter: 5/32" (4.0 mm)
- Standard length: 18" (45.7cm)
- Custom lengths available

## MARKING/PRINTING

- Laser Printing: Name, logo, consecutive numbers, barcode

## STANDARD COLORS

- Red, Blue, and Green



## PACKAGING

- Standard: 250 seals per carton
- Carton dimensions: 14.2"x 11"x 7.9" (36cm x 28cm x 19cm)
- Weight: 35.3 lb (16 kg)

