



FlexSecure FS35

The FlexSecure FS35 rates High Security per the ISO 17712:2013 testing standard and is C-TPAT and PIP compliant. This versatile seal fits many applications and is popular for sealing bulk railcars and intermodal containers and trailers. The non-preform 1/8" cable frays wildly when cut and is galvanized for corrosion protection. The patent pending locking mechanism inside the anodized aluminum housing makes sure your goods are safe in transit.

C-TPAT & PIP COMPLIANT



APPLICATIONS

- Cross Border Shipments
- Container Door Latches
- High Value Shipments
- Rail Cars
- Trailer Door Latches

FEATURES

- ISO 17712 classification - High Security
- Tamper-evident non-preformed steel cable unravels when cut and is galvanized for corrosion protection
- Customized laser printing name/logo/consecutive numbers and barcode

MATERIAL


- Main body: Aluminum alloy
- Internal Locking Components: Zinc and Steel
- Cable: 1/8" galvanized non-preformed aircraft cable

STRENGTH CHARACTERISTICS

- Average pull apart strength: 2400 lbs.(1088kg)

DIMENSIONS

Body: 1.12" x .90" x .30" (28.6 mm x 22.7 mm x 7.6 mm)
 Cable Diameter: 3.2 mm (1/8")
 Overall length: Standard 12" (Custom lengths available)



FlexSecure FS35

MARKING/PRINTING

Laser Printing: Name, logo, consecutive numbers, barcode.

STANDARD COLORS

Red / Blue / Black / Green



PACKAGING

Standard: 10 per tray

200 seals per carton

Box dimensions: 22"x 10"x 8" (56cm x 25cm x 20cm)

Weight: 18 lbs. (8.25 kg)

